

# Leica Lino line lasers

## Technical data sheet



### Delivery package Leica Lino L2:

Art. No. 757225

- Leica Lino L2
- Target plate for red lasers
- Magnetic multifunction adapter
- Ball adapter for tripod
- Alkaline batteries (type AA, 3 × 1.5V)
- Carrying pouch



### Delivery package Leica Lino L2+:

Art. No. 783711

- Leica Lino L2+
- Target plate for red lasers
- Magnetic multifunction adapter
- Alkaline batteries (type AA, 4 × 1.5V)
- Carrying case and pouch



### Delivery package Leica Lino L2G+:

Art. No. 817856

- Leica Lino L2G+
- Target plate for green lasers
- Magnetic multifunction adapter
- Alkaline batteries (type AA, 4 × 1.5V)
- Carrying case and pouch



### Delivery package Leica Lino L2P5:

Art. No. 777069

- Leica Lino L2P5
- Target plate for red lasers
- Magnetic multifunction adapter
- Alkaline batteries (type AA, 4 × 1.5V)
- Carrying case and pouch



### Delivery package Leica Lino L360:

Art. No. 790509

- Leica Lino L360 Line Laser
- Target plate for red lasers
- Mini tripod adapter
- International charger with 4 plugs
- Carrying case

Technical Data	Lino L2	Lino L2+	Lino L2G+	Lino L2P5	Lino L360
Range*	up to 30 m				
Range with laser receiver*	up to 60 m				up to 70 m
Levelling accuracy	± 1 mm @ 5 m	± 1,5 mm @ 5 m			
Self-levelling range	4° ± 0,5°				3,5° ± 0,5°
Number of laser dots				4	
Number of laser lines	2				
Beam direction	vertical, horizontal			vertical, horizontal up, down, right, left	vertical, horizontal
Accuracy of plumb points @ 5 m				± 1,5 mm	
Accuracy of horizontal line @ 5 m	± 1,5 mm				
Vertical accuracy @ 3 m line length	± 0,75 mm				
Beam divergence	< 120°	< 180°			360° (horizontal)
Laser type	635 nm, laser class 2		515-520 nm, laser class 2	635 nm, laser class 2	
Battery type	type AA 3 × 1,5 V	type AA 4 × 1,5 V			NiMH battery pack
Battery life	up to 8 hours (alkaline)	up to 12 hours (alkaline)	up to 7 hours (alkaline)	up to 10 hours (alkaline)	up to 20 hours (rechargeable)
Protection class	IP 54				IP 65
Operating temperature	-10°C to 40°C		0°C to 40°C	-10°C to 40°C	
Dimensions (H × D × W)	96 × 91 × 54 mm	117,8 × 130,7 × 75,4 mm			131,7 × 145 × 96,2 mm
Weight with batteries	390 g	530 g			1009 g
Tripod thread	1/4"				

\*) depending on lighting conditions



Laser class 2 in accordance with IEC 60825-1